# **Collection and Presentation of Crash Data**

Transportation Planning Branch



Approved: August 30, 2007 Revised: November 20, 2012

Version 4

## [Contents]

**Purpose** 

**Background** 

Responsibility

Policy, Regulatory, and Legal Requirements

Scheduling and Time Constraints

**Procedures** 

Warnings and Precautions

Resources and Tools

Contacts

Glossary

**User Access** 

**Flowchart** 

Record of Revision

## **Purpose**

The purpose of this procedure is to provide a consistent methodology for gathering information about the status of vehicle crashes in the study area, and presenting that information for CTP studies.

## **Background**

Traffic crash data can reveal whether transportation improvements may increase safety. Some causes of crashes cannot be impacted by transportation improvements, such as those that result from driver or vehicle performance, or the weather. Types of crashes that may be reduced by transportation improvements include those due to traffic conditions or roadway characteristics. For example, traffic crashes may be an indicator of congestion problems that can be reduced by capacity adding projects or congestion management strategies. Crashes may also be a result of the physical characteristics of the roadway like substandard design, inadequate signing, ineffective parking, or poor sight distance. Some of these crashes may be prevented with physical design or traffic control changes such as the installation of stop signs or traffic signals. There type of crash data utilized in this procedure is high frequency crash locations. The Traffic Safety Unit of NCDOT's Transportation Mobility and Safety Division identifies high frequency crashes at intersections and along roadway sections. High frequency crash location data is available on the NCDOT's Traffic Safety Unit website.

# Responsibility

It is the responsibility of the Project Engineer to obtain the crash data and put the appropriate data into a standardized map in the Comprehensive Transportation Plan (CTP) Report.

# Policy, Regulatory, and Legal Requirements

No specific policy exists for the collection of crash data for CTP studies.

# Scheduling and Time Constraints

The collection of crash data should be completed before the deficiency analysis is conducted on the highway system as a whole, as part of the CTP study.

### **Procedures**

The project engineer will follow the steps below to properly collect and map highway crash data for the study planning area.

ncy crash data to e high frequency? Report (refer to Problem Statement' eps. In the Crash of Metadata, Maps, save both
e high frequency Report (refer to Problem Statement' aps. In the Crash : 01 Metadata, Maps,
: 01 Metadata, Maps,
napefiles to the CTP
equency Crash terial. This map sh data and an the same webpage select +Crash Type: Select the map for
ld be clipped to your
o 10_CTP Map
o create the <b>High</b> ropriate layers from gend to reflect your ta according to the
> Categories > ply symbology using
ар 10_СТР Мар
line width =1.5, for dy Roads >Properties

Select the Crash Intersections layer, open Properties > Symbology > Categories > 6 Unique Values and select field Category. Add all values and apply symbology using the most current CTP Style File S:\Shared\TPB Reference\Comprehensive Transportation Plan\ArcMap 10\_CTP Map Templates & Style File\ArcMap10\_CTP\_Style\_(September\_2012).zip See example of the map legend below. **HFCL Map Color and Shape** Sample Legend for High Frequency **Standards** Crash Locations Colors In Order: FIGURE X Electron Gold Area Name Dark Ameythist Comprehensive Transportation Plan Poinsetta Red HIGH FREQUENCY **CRASH LOCATIONS** Peacock Green January 1, 2006 to December 31, 2010 Ultra Blue Crash Intersections 50 and above ▲ 40 to 49 Light Apple ■ 30 to 39 20 to 29 Intersections - Shape Size = 12 10 to 19 4 to 9 50 and above Crash Sections - 50 and above ▲ 40 to 49 - 40 to 49 - 30 to 39 **30** to 39 - 20 to 29 - 10 to 19 20 to 29 4 to 9 Study Roads 10 to 19 Roads 4 to 9 Schools Ferry Airports Railroads Sections - Line Width = 1.5 Rivers and Streams Water Bodies Municipal Boundaries 50 and above County Boundary - 40 to 49 - 30 to 39 - 20 to 29 - 10 to 19

4 to 9

# Warnings and Precautions

None

### Resources and Tools

- Develop CTP Maps procedure
- Adobe Acrobat Reader
- ArcMap (ESRI software)
- ArcCatalog (ESRI software)
- NCDOT Traffic Safety Unit website

#### **Contacts**

- For suggestions to change this procedure contact: Elena Talanker (919) 707-0911
- For questions about performing this procedure contact: Elena Talanker (919) 707-0911

## Glossary

For a complete listing of terms, definitions and acronyms, go to the Master Glossary.

### **User Access**

Intended for NCDOT Internal Use Only, but not exempt from the public records access requirements.

### **Flowchart**

None

#### Record of Revision

Version	Section Affected	Description	Effective Date
2	Procedures	The threshold for the minimum number of crashes was changed from 5 to 10. Some additional links were activated.	07/24/09
	Background, Procedures	Added 'Requesting a Crash Analysis from NCDOT's Safety Planning Group' section to the Procedures and reference to it in the Background and other edits. Added map developing guidance in the map preparation procedure.	07/21/2010
3.1	Links	Updated broken links to Crash Data from NCDOT's Safety Planning Group	07/21/2011

4	Procedures	Whole procedure was changed to utilize	11/20/2012
		HFCL Intersections and Sections data	
		available from the Transportation Mobility and Safety Division website.	